



Westix Adhesives
Div. of Western American, Inc.
1518 Taney St. North Kansas City, MO 64116

Phone: 816.421.3000 | Fax: 816.421.3122 | www.westix.net

ST16 Product Bulletin

GENERAL INFORMATION

ST16 was formulated as a transparent; clear drying, General Purpose, Hot Melt Adhesive. Suggested uses include Wood, Corrugated, and Fabric.

| | |
|--------------------------------|---|
| Application Temperature | 350°- 375°F |
| Viscosity at 350° F | 14,000 ± 500 cps. @ 350°F |
| Melt Point | 182° F ± 5° F |
| Set Speed | Medium to Slow |
| Product Form | Hot Melt Glue Sticks |
| Packaged | 25 lbs. per Carton 1200 lbs. per Pallet |
| Shelf Life | 3 plus years |

Components contained in this product conform to USDA and FDA regulations for use in food packaging, as stated in the Federal Food and Drug and Cosmetic Act, Title 21 under section 175 - 105. This guarantee is also intended to comply with USDA's "Policy Governing Inspection of Packaging Materials".

Note: The data presented is based upon tests believed to be reliable; however, Western American, Inc., does not guarantee their accuracy
Or completeness. Western American, Inc., assumes no responsibility for results obtained or for incidental or consequential damages arising
From the use of this data.