



## MATERIAL SAFETY DATA SHEET HOT MELT ADHESIVES

Prepared Date: 02/14/2014

---

### SECTION I

---

MANUFACTURED BY: Western American, Inc  
1518 Taney Street  
North Kansas City, MO 64116  
TELEPHONE: 816-421-3000  
CONTACT: Rick Hennig  
PRODUCT CLASS: Hot Melt Adhesive  
MANUFACTURER'S CODES: **ST195**

---

### SECTION II - HAZARDOUS INGREDIENTS

---

Paraffin Wax Fume CAS# 8002-74-2 NIOSH REL: TWA 2mg/m<sup>3</sup>  
ACGIH TLV: 2mg/m<sup>3</sup> (TWA)

---

### SECTION III - PHYSICAL DATA

---

BOILING POINT - N/A SPECIFIC GRAVITY - 0.92  
VAPOR PRESSURE - N/A MELTING POINT - 160 - 230  
VAPOR DENSITY - N/A EVAPORATION RATE - N/A  
SOLUBILITY IN WATER - INSOLUBLE  
APPEARANCE AND ODOR - AMBER PELLETS

---

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

---

DOT CATEGORY - NON FLAMMABLE FLASH POINT - 450F  
EXTINGUISHING MEDIA - CO<sub>2</sub>

SPECIAL FIRE FIGHTING PROCEDURES - NONE  
UNUSUAL FIRE AND EXPLOSION HAZARDS - NONE

---

### SECTION V - HEALTH HAZARD DATA

---

MAIN ROUTE OF ENTRY - INHALATION, PROVIDE ADEQUATE VENTILATION  
TARGET ORGANS - NONE  
HEALTH HAZARDS (ACUTE AND CHRONIC) - NONE

CONTACT WITH MOLTEN MATERIAL WILL CAUSE THERMAL BURNS TO SKIN AND EYES



Westix Adhesives  
Div. of Western American, Inc.  
1518 Taney St. North Kansas City, MO 64116

Phone: 816.421.3000 | Fax: 816.421.3122 | www.westix.net

Product: **ST195**

**FIRST AID:**

**COOL AFFECTED AREA IMMEDIATELY, OBTAIN MEDICAL ASSISTANCE, DO NOT ATTEMPT TO REMOVE COOLED ADHESIVE FROM SKIN, AS IT WILL SEVERELY DAMAGE SKIN**

---

**SECTION VI - REACTIVITY DATA**

---

STABILITY - STABLE

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS - CARBON MONOXIDE

CONDITIONS TO AVOID - TEMPERATURES OVER 400F MAY CAUSE RESIN DEGRADATION

HAZARDOUS POLYMERIZATION - CANNOT OCCUR

---

**SECTION VII - SPILL OR LEAK PROCEDURES**

---

SPILL - SWEEP UP MATERIAL TO PREVENT SLIPPING, ALLOW MOLTEN SPILLS TO COOL BEFORE SCRAPING UP AND DISPOSING.

WASTE DISPOSAL METHOD - IN ACCORDANCE WITH LOCAL REGULATIONS

---

**SECTION VIII - PROTECTIVE EQUIPMENT TO BE USED**

---

VENTILATION - YES, PROVIDE ADEQUATE VENTILATION, DO NOT USE IN CONFINED SPACES

PROTECTIVE GLOVES - YES

EYE PROTECTION - YES

---

**SECTION IX - PRECAUTIONS OR OTHER COMMENTS**

---

STORAGE AND HANDLING - STORE IN COOL DRY PLACE, OPTIMUM TEMPERATURE 70 F.

PICK UP MATERIAL IMMEDIATELY TO ELIMINATE SLIPPING HAZARDS.